



## Solid Braid (Sash Braid) Nylon

Manufactured from high tenacity nylon 6.

Diameter	Weight (lb/100')	MBS	Available Packages	PART #
3mm (1/8")	0.5lb	400lbf	250ft Reel / 1,000ft Reel	04-040
4mm (5/32")	0.7lb	500lbf	250ft Reel / 1,000ft Reel	04-050
5mm (7/32")	1.0lb	700lbf	250ft Reel / 1,000ft Reel	04-060
6mm (1/4")	1.6lb	1,100lbf	250ft Reel / 1,000ft Reel	04-080
8mm (5/16")	2.5lb	1,960lbf	250ft Reel / 1,000ft Reel	04-100
10mm (3/8")	4.0lb	5,000lbf	250ft Reel / 600ft Reel	04-120
12.7mm (1/2")	5.2lb	7,000lbf	250ft Reel / 600ft Reel	04-160

\*Rated breaking strength is the optimum strength, achieved under laboratory conditions, in accordance with prescribed test procedures, on a new rope, pulling at a slow, steady rate in a straight line.

### Applications

- General Purpose / Industrial
- Tie Downs
- Flagpoles

### Features

- Maintains shape through use
- Non-rotating torque free design
- Excellent knotting

### Fiber Specifications

- Good UV resistance
- Excellent microbial resistance
- Melts at 218°C

Specifications may change without notice. We recommend referring to [cancord.com](http://cancord.com) for the most up to date information, or requesting a current specification sheet when ordering.



Revision 2024-09