



3 Strand Nylon

Manufactured from high tenacity UV stabilized nylon 6, these ropes are a medium lay 3 strand twisted construction.

Diameter	Weight (lb/100ft)	MBS	Available Packages	PART #
5mm (3/16")	1.1lb	1,400lb	300ft / 600ft / 1,200ft	59-060
6mm (1/4")	1.7lb	2,000lb	300ft / 600ft / 1,200ft	59-080
10mm (3/8")	3.6lb	3,700lb	300ft / 600ft / 1,200ft	59-100
12mm (1/2")	6.3lb	6,000lb	300ft / 600ft / 1,200ft	59-120

*Rated breaking strength is the optimum strength, achieved under laboratory conditions, in accordance with prescribed test procedures, on a new rope, pulling at a slow, steady rate in a straight line.

Colours available from stock include: white, black, yellow, green, red, royal blue, orange, coyote brown, burgundy, hunter green, grey, gold, neon green, neon pink, neon turquoise, navy, pink & purple.

Applications

- General Purpose / Industrial
- Pulling Lines
- Marine

Features

- Non-rotating torque free design
- Spliceable
- Excellent knotting

Fiber Specifications

- Excellent weather resistance (including UV)
- Excellent microbial resistance
- Melts at 218°C

Specifications may change without notice. We recommend referring to cancord.com for the most up to date information, or requesting a current specification sheet when ordering.



Revision 2026-05