



Bull Rope Specifications & Technical Data

Manufactured from high tenacity polyester & finished with a proprietary coating process for added abrasion & cut resistance.

Diameter	Weight (lb/100')	MBS	Elongation (at 10% of MBS)	Colour	Available Packages	PART #
13mm	7.4lb	9,500lbf	3%	Blue/Yellow	100' / 200' / 600'	03-713
14mm	9.5lb	10,900lbf	4%	Yellow/Black	100' / 200' / 600'	03-714
16mm	11.4lb	13,000lbf	4%	Black/Yellow	100' / 200' / 600'	03-716
19mm	21.8lb	21,000lbf	4%	Purple/Orange	100' / 200' / 600'	03-719

*Rated breaking strength is the optimum strength, achieved under laboratory conditions, in accordance with prescribed test procedures, on a new rope, pulling at a slow, steady rate in a straight line.

Applications

- Rigging
- Pulling
- Tree removal

Features

- High strength, abrasion resistant & durable
- Non-rotating torque free design
- Static

Fiber Specifications

- UV resistant
- Excellent microbial resistance
- Melts at 254°C

Specifications may change without notice. We recommend referring to cancord.com for the most up to date information, or requesting a current specification sheet when ordering.

Custom colours & lengths available on a made to order basis. Please contact info@cancord.com for details.



Revision 2025-01